



PLATES

SRAPIASIC..

**INTERMEDIATE ANCHOR
PLATE INSULATED 50 mm
- INTERNAL STAINLESS
STEEL AISI 316L AND
EXTERNAL NATURAL
COPPER**

It is used as start of the chimney from a cantilever bracket or from a preformed concrete lintol. It allows the passing from two twin wall chimneys.

Di	De	H1	H2	A	H
80	180	98	35	280	190
100	200	98	35	300	190
130	230	98	35	330	190
150	250	98	35	350	190
180	280	98	35	380	190
200	300	98	35	400	190
250	350	98	35	450	190
300	400	98	35	500	190
350	450	98	35	550	190
400	500	98	35	600	190
450	550	98	35	650	190
500	600	98	35	700	190
550	650	98	35	750	190
600	700	98	35	800	190
650	750	98	35	850	190
700	800	98	35	900	190
750	850	98	35	950	190
800	900	98	35	1000	190

EN 1856-1 T200 P1 W V2 L50040 O30
EN 1856-1 T600 N1 W V2 L50040 O30 G50

The records, the specifics and the representations of the following catalogue are undemanding. Expo Inox S.p.A. reserves the right to introduce, at any time, the modifications that considers necessary.

www.expoinox.com

Kamini

Inox