



## PLATES

EEXPIASIC..

**INTERMEDIATE ANCHOR  
PLATE INSULATED 25 mm  
- STAINLESS STEEL AISI  
304**

*It is used as start of the chimney from a cantilever bracket or from a preformed concrete lintol. It allows the passing from two twin wall chimneys.*

Di	De	H1	H2	A	H
80	130	98	35	230	190
100	150	98	35	250	190
130	180	98	35	280	190
150	200	98	35	300	190
180	230	98	35	330	190
200	250	98	35	350	190
250	300	98	35	400	190
300	350	98	35	450	190
350	400	98	35	500	190
400	450	98	35	550	190
450	500	98	35	600	190
500	550	98	35	650	190
550	600	98	35	700	190
600	650	98	35	750	190
650	700	98	35	800	190
700	750	98	35	850	190
750	800	98	35	900	190
800	850	98	35	950	190

**EN 1856-1 T200 P1 D VM L20040 O30  
EN 1856-1 T600 N1 D VM L20040 O50 G70**

The records, the specifics and the representations of the following catalogue are undemanding. Expo Inox S.p.A. reserves the right to introduce, at any time, the modifications that considers necessary.

[www.expoinox.com](http://www.expoinox.com)

**Kamini**

Inox