



| Di  | De  | A    | B  | H   |
|-----|-----|------|----|-----|
| 80  | 180 | 320  | 65 | 230 |
| 100 | 200 | 320  | 65 | 230 |
| 130 | 230 | 400  | 65 | 230 |
| 150 | 250 | 400  | 65 | 250 |
| 180 | 280 | 400  | 65 | 250 |
| 200 | 300 | 500  | 65 | 270 |
| 250 | 350 | 600  | 65 | 270 |
| 300 | 400 | 720  | 65 | 300 |
| 350 | 450 | 720  | 65 | 300 |
| 400 | 500 | 850  | 65 | 330 |
| 450 | 550 | 850  | 65 | 330 |
| 500 | 600 | 850  | 65 | 330 |
| 550 | 650 | 1150 | 65 | 350 |
| 600 | 700 | 1250 | 65 | 370 |
| 650 | 750 | 1350 | 65 | 380 |
| 700 | 800 | 1400 | 65 | 390 |
| 750 | 850 | 1450 | 65 | 400 |
| 800 | 900 | 1500 | 65 | 410 |



## TERMINALS

SEXCCDPC..

**RAIN CAP INSULATED 50 mm - INTERNAL STAINLESS STEEL AISI 316L AND EXTERNAL AISI 304**

*It is placed on top of the chimney to protect from rain ingress*



The records, the specifics and the representations of the following catalogue are undemanding. Expo Inox S.p.A. reserves the right to introduce, at any time, the modifications that considers necessary.

[www.expoinox.com](http://www.expoinox.com)

**Kamini**

Inox